


The information disclosed herein is the property of the originator who reserves all patent, design, proprietary, manufacturing, use and sales rights thereto, except for the rights expressly granted to others. This document shall not be reproduced nor shall the information contained within be used by or disclosed to others except as expressly authorized by the originator. ©

Revision Letter	Change Description

1" [25.4mm] O.D. x 3/8" [9.5mm] I.D. x .090" Thick Steel Washer




Engine Mount Pin Typical for AeroVee, 4 Required per Mount
Weld together using Number 7 welding rod
Full Scale

1/4" ID x 1" OD x 1/8" Thick Washers
 4 Required on -01 / -02

ACV-A01-01 AeroVee Engine Accessory Plate Reference

Mount Pin on Welded Motor
 Mount Assembly Reference

AN4-36A Bolt, 4 Required on -01/-02
 AN960-416 Washer, 8 Required on -01/-02
 AN363-428 Nut, 4 Required on -01/-02



Typical Detail of Engine Mount Cushions & Bolts
Typical 4 Locations

ACV-P01-19 Shock Absorber Bushing
 4 Sets required

Note: Corrections to the Engine Alignment (Propeller Hub Location) may be made by using Spacers under to Rubber Cushions. The maximum Spacer thickness on any one mount is 1/16" [1.6mm]

Sonex Aircraft, LLC		
AeroVee Mount Pin Detail and Typical Installation		
Drawing Scale FULL	Drawing Number SNX-P31-03	Revision N/C